

Stonehenge Porcelain



A brushed, roughhewn and weathered effect are the elements of inspiration in the new **Stonehenge Porcelain**. This collection is offered in two sizes with a lappato or honed finish, capturing the ancient landscape in this spiritually acclaimed wonder of the world. GREENGUARD Certified, interior or exterior use, for walls and floors all make this a go-to product for any iconic design.

Tiles - Spec ID#'s are listed for 12" x 24"



Amsbury
Honed: FLSRB021
Lappato: FLSRB020



Shrewton
Honed: FLSRB023
Lappato: FLSRB022



Tidworth
Honed: FLSRB025
Lappato: FLSRB024



Salisbury
Honed: FLSRB017
Lappato: FLSRB016




Thrupton
Honed: FLSRB019
Lappato: FLSRB018




Installation Photo
Featuring Stonehenge Porcelain - Shrewton - Honed - FLSRB023

Mosaics



2" x 2" Mesh
Mounted on
12" x 12" Sheet



1" x 2" Mesh
Mounted on
12" x 12" Sheet

Trim Pieces



Bullnose
4" x 24"



Cove Base
6" x 12"

View collection web page for the complete offering including additional product options, corresponding Spec ID# and updates.

SPECIFICATIONS

SIZE: 18" x 36", 12" x 24" nominal; **Spec ID#'s are listed for 18" x 36";** **Mosaics:** 2" x 2" or 1" x 2" on a 12" x 12" Mesh Mounted Sheet

THICKNESS: 3/8" nominal

FINISH: Honed, Lappato; **18" x 36" Amsbury, Salisbury, Thrupton and Tidworth available in Honed only**

APPLICATION: Floors and Wall; Interior and Exterior

HEALTH AND WELLNESS: Proprietary antimicrobial and anti-pollution coating is available with a 5000 sq.ft. minimum

- Trim Pieces Available
- Made in the USA
- GREENGUARD Gold Certification
- Can contribute to LEED®
- In Stock products are subject to availability
- Please note that variations in color and texture may occur due to the nature of the material

How to make holes:

It is necessary to use a water milling cutter or a continuous crown diamond-cutting disk for stoneware and granite tiles. After having penciled (6) – on the back of the product – the perimeter of a square within which the hole must be made, use the cutting tool to cut perpendicular and diagonal lines and then concentric circles towards the outside (7). The pictures at the side illustrate in detail the cuts to follow. When the central thickness of the hole has become very thin, turn the piece over and open up the hole by tapping lightly (8).

For holes in tiles a diamond point's drill for granite must be used. It is important to remember to cool the points often while working.



6

7

8

MAINTENANCE

Quality

ASI products are produced using the highest quality standards and the finest available raw materials. Glazed and unglazed porcelain products marketed under the manufacture trademarks are fully vitrified, resulting in extreme durability, hardness, and low water absorption. ASI products are highly stain and wear resistant. However, as with every surface material, a basic cleaning and maintenance program should be followed to maintain a satisfactory appearance and an acceptable level of performance.

Care During Construction

ASI products are classified as a finish material. As such they should not be installed until after any heavy construction work has been completed. In instances where the ASI products are installed prior to the completion of construction special care must be taken to protect the tile until it is put into normal service. The general buildup of dirt and debris present on any construction site may negatively affect the performance of the tile if it is left unprotected. The best way to protect the tile surface is to cover it with a protective layer of Kraft paper, carpeting, cardboard, plywood, or any other material that will not adversely affect the tile surface.

Initial Cleaning and Maintenance

The most important cleaning operation is performed immediately after the tile has been set. This involves the complete removal of grout residue and construction dirt from the newly installed ASI products. Grout manufacturers provide directions for the cleanup of their products after installation has been completed. These directions should be followed. In many cases ASI products can be successfully cleaned by scrubbing with a mild detergent, combined with a thorough rinsing. It is critical that all rinse water be removed through wet vacuuming or dry toweling. Should any grout residue remain this process can be repeated several times as necessary.

For highly textured products, or when using a dark colored grout with a light-colored tile, a grout release may be used prior to grouting to assist in the removal of the grout from the surface of the tile. Before grouting, the contractor should test a small area of the tile to determine if the chosen color grout will discolor the surface of the tile, in which case a grout release should be utilized. Please follow the specific manufacturer's instructions for the use of any grout release product.

Surface Coatings

The inherent density and low water absorption of all ASI products ensure a product that is easy to maintain. ASI products do not require the use of sealers or waxes. These surface coatings may negatively affect the performance of the tile.

In some instances where an unglazed, polished porcelain product is used in an area subject to excessive exposure to dirt, a penetrating type sealer may be used. A penetrating sealer is designed to fill the microscopic pores created during the polishing process. It is not designed to coat the surface of the tile.

We recommend that all sealers be tested in a small inconspicuous area before general use on the floor. Please ensure you follow the manufacturer's instructions when using a penetrating sealer and do not allow the sealer to dry on the surface of the tile.

Regular Maintenance

The inherent technical characteristics of ASI products ensures that they will be relatively easy to maintain and should provide years of enjoyment. Many general-purpose cleaners that are readily available are acceptable for use on ASI products. It is important that the cleaner has a non-oil, non-animal fat, non-soap base. These components can leave behind an invisible residue which can trap dirt. It is also important that the tile receive a thorough rinsing with clean water after the cleaning process has been completed.

The general cleaning steps for ASI products can be summarized as follows:

1. Remove all loose debris from the tile by sweeping with a soft bristle broom or vacuuming.
2. Any spills should be wiped up as quickly as possible.
3. Apply the recommended amount and dilution of the appropriate cleaner to the tile. Allow the cleaner to remain on the tile for short period of time (at least 5 minutes).
4. For unpolished tile, scrub with a nylon pad or soft bristle brush. For more heavily soiled floors a floor machine equipped with a nylon pad or bristle brush may be used. For polished tile, wipe or mop with a nonabrasive mop or cloth.
5. Remove the dirty cleaning solution and water with a wet vacuum or mop. Thoroughly rinse the tile with clean water and remove with a wet vacuum, mop, or towel. It is essential
6. for all detergent residues to be completely removed from the tile. Any remaining detergent residue can dry on the tile and form a coating which can trap dirt and be very difficult to remove. The tile should be rinsed several times if necessary, to remove all detergent residue.

The frequency and timing of any maintenance program is dependent on the specific characteristics of each tile application. Factors such as foot traffic, environmental conditions and product color should be considered when planning your maintenance schedule. In high traffic areas, or in areas subject to excessive exposure to dirt, a more frequent cleaning schedule may be necessary.

A Word About Cleaners

There are many excellent cleaners on the market today which should provide you with satisfactory results. All-purpose household cleaners such as Soft Scrub, Top Job, Mr. Clean, Ajax Liquid, Dow Bathroom Cleaner, Liquid Comet, and Fantastik are all suitable for general purpose cleaning of Aegean products. Soap less detergents such as Spic & Span and 409 may also be used.

For the removal of stains on unpolished tile, scouring powders such as Comet, Bon Ami, or Ajax may be used. These may be used in conjunction with a nylon pad or soft bristle brush. Steel wool is not recommended.

For heavier cleaning requirements or commercial applications, products manufactured by Aqua Mix, Hillyard Industries, Walter G. Legge Co., or CeramaSeal may be used. These products are available through your local ceramic tile dealer. In all cases please ensure you follow the manufacturer's instructions. We also strongly recommend that all cleaners be tested first in a small, inconspicuous area before general use on the floor.

WARRANTY

1 year limited Commercial and or Residential warranty

- ASI warranty that its products meet or exceed the performance specification outlined in ANSI A137. Our porcelain is first quality product that is provided through the production facility.
- Approved use for Commercial and residential projects and installations
- Our products should be examined prior to installation
- Missuses of the product by the purchaser including; negligence, physical or chemical abuse is not covered thy this warranty
- Installation defects are not covered by this warranty
- Visual defect or non-conformities apparent prior to installation are not covered thy this warranty
- This warranty will cover our products purchased by a residential or commercial user for up to 12 months from the date material is shipped
- Certain factors on a jobsite are beyond our control; installation, structural design & environmental conditions
- In the event of latent defects caused by improper manufacture, defined as tiles not conforming to industry standards, ASI will either refund the price for the defective pieces or provide replacement material of the same kind. ASI will not be responsible for any costs of labor, installation and/or removal of our products.
- ASI does not warrant that our glazed and unglazed porcelain will not scratch, chip or show signs of wear.

ASI makes no implied warranties of merchantability or fitness for a particular purpose or any other warranties expressed, or implied warranties implied, except as otherwise set forth above. Under no circumstances shall ASI be liable for incidental or consequential losses, damages, or expenses, directly or indirectly arising from the sale, handling or use of our products. No consequential (including loss of profits) or incidental damages are recoverable.

TECHNICAL DATA

Physical Properties	ASTM Test	Industry Standards	Results
Water Absorption	C373	Impervious <0.5%	≤ 0.1%
Thickness Dimension	C499	Range ±0.04in Max.	≤ ±0.04 in
Facial Dimension	C499	±0.25%	≤ ±0.25%
Warpage Average	C485	± 0.40% on any edge	≤ ± 0.40%
Warpage Average	C485	± 0.40% on diagonal	≤ ± 0.40%
Wedging Average	C502	± 0.25%	≤ ± 0.25%
Bond Strength	C482	≥ 50 psi	≥ 200 psi
Breaking Strength	C648	≥ 250 lbf	≥ 400 lbf
Hardness (Mohs)	Scratch Test (No regulated)	Range 0 - 10	≥ 7
Visible Abrasion Resistance for Glaze Tile	C1027	No requirement Range 0 - 5	Class 4
Frost Resistance (Freeze/Thaw)	C1026	No sample must show alterations to surface	No evidence of damage
Chemical Resistance	C650	No Requirement Range E - A	Class A
Stain Resistance	C1378	No Requirement Range E - A	Class A*
Coefficient of Friction (Dynamic)	DCOF Acutest sm (wet)	≥ 0.42	≥ 0.42*
Aesthetic Classification	Visual Evaluation Shade & Texture	No Requirement Range V0 – V4	V2